

System Requirements IsoCompose 2

For IsoCompose 2 for Windows we recommend

- **IBM compatible PC with Pentium processor:**
200 MHz CPU or faster
64 MB RAM or more, 50 MB free hard disk space
- **Graphics card:**
16Bit color screen resolution (High Color)
Minimum screen resolution 800x600 pixel
- **Required operating system:**
Windows® 98, 2000, XP
- **Further requirements**
Adobe Type Manager® Version 4.0 or higher (required for working with PostScript fonts)
Depending on the operating system a parallel or USB interface is needed to connect the hardware protection key (dongle).

For IsoCompose 2 for Macintosh we recommend

- **Apple Power Macintosh:**
266 MHz CPU (ITEDO recommends a G3 or faster)
64 MB RAM or more, 50 MB free hard disk space
- **Graphics card:**
16Bit color screen resolution (High Color)
Minimum screen resolution 800x600 pixel
- **Required operating system:**
Mac OS version 9.0 to 9.x and
Mac OS X as from version 10.1.3 in the Classic environment
- **Further requirements**
Adobe Type Manager® Version 4.0 or higher (required for working with PostScript fonts)
USB interface to connect the hardware protection key (dongle)

IsoDraw 5.1.04 or higher

IsoDraw 5 CADprocess 3 or higher

Please note:

With IsoCompose 2 for Macintosh you can edit parts lists and illustrations as well as the layout. The finished catalog however can only be viewed on a PC, since it is displayed with Internet Explorer and IsoView. IsoView is only available for the PC platform, since the distribution within the companies and through the companies is almost exclusively handled on PC platforms.

The creation of the graphics and preparation of the catalog however is often done on the Macintosh, especially by service providers. For this reason, we also provide a Mac version of IsoCompose. Thus, you can create the layout and generate the catalog on your Mac and then copy the files to a PC for viewing.

Do you have further questions? We will be happy to assist you.

Your ITEDO Software Team